

MIA



location:



SPECIFICATIONS:

DESCRIPTION

2-4 light vanity luminaires featuring handcrafted glass.

LAMPING

Standard: 40W Low-pressure G9 Halogen 120V lamp, included. Suitable for use in an open fixture. Dimmable with standard incandescent dimmer.

LED: 5W LED Replaceable source 120V, dimmable, included.

DIFFUSER

Shade shall be handcrafted glass of various decors. 5.0" Dia. x 4.5" H, spaced 7.875" apart on center.

CONSTRUCTION

Fixture utilizes metal arm assembly and stamped steel body, with plated finish. Decorative finials can be removed for downlighting applications. Decorative outlet box cover optional when not required.

METAL FINISH

Fixture shall be finished in Bronze, Chrome or Satin Nickel.

MOUNTING

Installs directly to a 4" octagonal outlet box, with 1.75" left or right offset. Canopy allows direct wiring without outlet box, where armored cable or non-metallic sheathed cable is employed, and the decorative outlet box cover is not required. Orient upward or downward, wall-mount only.

LABELS

UL or ETL Listed. Suitable for Damp Locations (interior use only).



MIA SHOWN IN HALVA (1779HV) IN BRONZE FINISH



For ordering information, see next page

All dimensions provided are nominal.
Allowance must be made for dimensional tolerance in handcrafted glasses.

REV 7/15




MIA

VANITIES WALL

ORDERING:


FIXTURE - GLAS		S OPTIONS	- METAL FINISH		- METAL FINISH		- OPTIONS	
2SW 2 Light Vanity 3SW 3 Light Vanity 4SW 4 Light Vanity	177907 177918 177919 177941 177980 177986 1779CE 1779CF 1779GF 1779HB 1779HN 1779HV	Opal Matte Amber Cloud Carrera Garnet Amber Matte Blue Cloud Ceylon Copper Foil Gold Foil Habanero Honey	(blank)	40W G9 Hal 5W LED 120V, dimmable	BR CR	TAL FINISH Bronze Chrome Satin Nickel	_	Square Canopy
	1779SF	Silver Foil						





Ex. 3SW-1779HV-SN

Mia 3-Light Vanity w/ Halva Glass, Satin Nickel Finish



4SW: 30.375"L

LED SCONCES:

- Total power of only 5 watts
- Dimmable with a standard dimmer
- Rated life: 25,000 hours
- 450 lumens
- CCT: 3000° Kelvin
- CRI: 80+

Canopy allows direct wiring without outlet box, where armored cable or non-metallic sheathed cable is employed, and the decorative outlet box cover is not required. Orient upward or downward, wall-mount only.

Project Informati	on:
-------------------	-----