

SAIL 13 / 17



SCONCES OUTDOOF

location:

SPECIFICATIONS:

DESCRIPTION

Wall-mounted **ADA-compliant** sconce featuring handcrafted glass.

LAMPING

Standard: 2x 40W B10 120V incandescent, lamp not included. Dimmable with standard incandescent dimmer (not included).

CFL: 26W 4-Pin CFL with non-dimming electronic ballast. 120V,

lamp not included.

LED: 9W Replaceable source, 120V, dimmable, 80+ CRI, 3000°K CCT, 800 lumens,

30,000 hours. Lamp included. (For Opal only)

LED Edison: 5W Replaceable S-Style LED Filament lamp, 120V, dimmable, 2200°K

CCT, 540 lumens, 15,000 hours, lamp included. (For Bubble only)

DIFFUSER

Diffuser shall be handcrafted Opal Matte or Bubble glass. Sail 17 features decorative faceplate and aluminum fitter.

CONSTRUCTION

Stamped aluminum fitter is powder coated white. Glass is secured by stainless steel set screws.

MOUNTING

Installs directly to a 4" octagonal outlet box. 75°C supply wire required for incandescent lamping. Fixture is centered on the outlet box. Wall mount only.

IARFIS

UL or ETL Listed. Suitable for Wet Locations (interior or exterior use).



SAIL 13 SHOWN IN SMOKE BUBBLE (7855SM) & SAIL 17 SHOWN IN BUBBLE/SILVER (SAIL17BB-SL)

785507-BK OPAL MATTE SAIL17SW-BR OPAL/BRONZE SAIL17SW-BK OPAL/BLACK



Project Information:

All dimensions provided are nominal. Allowance must be made for dimensional tolerance in handcrafted glasses.


REV 3/17


SCONCES OUTDOOR



ORDERING:







FIXTURE SAIL17BB Bubble glass w/ decorative faceplate SAIL175M Smoke Bubble glass w/ decorative faceplate

SAIL175W Opal glass
w/ decorative faceplate
785507 Opal glass only

78555M Smoke Bubble glass only **785550** Bubble glass only

LAMP OPTIONS - METAL FINISH (blank) 2x 40W B10 Incan BR Bronze

ank) 2x 40W B10 Incan BR Bronze
H1 1x 26W Quad 120V BK Black

Q1 1x 26W Quad 277V SL Silver EDIL 2x 5W LED Filament

(For Bubble Only)

LED 1x 9W LED 120V,
dimmable
(For Opal only)

Ex. SAIL17SW-BR

Sail 17 Sconce w/ Opal Glass with Bronze Faceplate,

Project Information: