



RISE

MINI SCONCES WALL

location:
DAMP

SPECIFICATIONS:

DESCRIPTION

Wall-mounted sconce featuring one handcrafted glass.

LAMPING

Standard: 60W A19 120V incandescent, suitable for dimming.

GU-24 CFL: Self-ballasted GU-24 lampholders. 13W max, 120V. lamps not included.

LED: 10W GU24 LED Lamp 120V, dimmable, included.

DIFFUSER

Shade shall be handcrafted Opal Matte glass.

3.5" x 3.5" x 4.75" H

CONSTRUCTION

Fixture utilizes die-cast arm assembly and stamped steel canopy (4.75" H), with plated metal finish.

METAL FINISH

Fixture shall be finished in Bronze, Chrome or Satin Nickel.

MOUNTING

Installs directly to a 4" octagonal outlet box.


Orient upward or downward, wall-mount only.

LABELS

UL or ETL Listed. Suitable for Damp Locations (interior use only).



RISE SHOWN IN OPAL MATTE (449807)



ORDERING:

FIXTURE	GLASS OPTIONS	LAMPING OPTIONS	METAL FINISH
1WZ Sconce	449807 Opal Matte	(blank) 60W A19 Incan GU24 13W GU24 120V LED 10W LED 120V, dimmable	BR Bronze CR Chrome SN Satin Nickel

Ex. 1WZ-449807-SN

Rise Mini Sconce w/ Opal Matte Glass, Satin Nickel Finish

Project Information:

LED SCONCES:

- Internal driver integrated in the lamp, GU24 base
- Total power of only 10 watts
- Dimmable with a standard dimmer
- Rated life: 30,000 hours
- Frosted acrylic diffuser
- 800 lumens
- CCT: 2800° Kelvin
- CRI: 80+

All dimensions provided are nominal. Allowance must be made for dimensional tolerance in handcrafted glasses.

REV 7/15