

OLIN

120V PENDANTS

location:

SPECIFICATIONS:

DESCRIPTION

Cord-hung or stem-mount pendant with handcrafted glass diffuser.

LAMPING

Standard: 60W T10 120V, not included.

Edison: 40W Edison Filament Medium-based, 120V, lamp included. **Plumen:** 11W Plumen CFL Medium-based, 120V, lamp included.

DIFFUSER

Shade shall be handcrafted glass of various decors. 7" Dia. x 11" H

SUSPENSION

Cord-hung: 10' SVT-type cord, complete with 5" decorative sleeve at the socketholder. Jacket coordinates with metal finish. Available on 1, 3 or 6 light canopies, shown on next page. Plated stamped steel construction. Bronze or Satin Nickel.


Stem-mount: 4 connectable stem sections (3", 6", 12" and 18" lengths), 10' max. 5" Dia. canopy (with swivel) and stem sections are plated steel. Bronze or Satin Nickel.

MOUNTING

Installs directly to a 4" octagonal ceiling box. Suitable for sloped ceilings.

LABELS

UL or ETL Listed. Suitable for Damp Locations (interior use only). Consult factory concerning lower wattage labeling for energy requirements.





OLIN SHOWN IN TRANSMIRROR (OLINTM)



For ordering information, see next page

All dimensions provided are nominal.
Allowance must be made for dimensional tolerance in handcrafted glasses.

REV 10/14



OLIN

120V PENDANTS

ORDERING:

CONNECTION -	GLASS OPTIONS	- LAMP OPTIONS	- METAL FINISH	OPTIONS
Cord Fixture	OLINAM Amber	(blank) 60W T10 Incan	BR Bronze	L 15' cord
1JC 1 Lt. Dome	OLINCL Clear	EDI 40W Edison	SN Satin Nickel	LW Low wattage
1JT 1 Lt. Flat	OLINTM Transmirror	PLU 9W Plumen		labeling

Stem Fixture 1TT 1 Lt. Flat

> Ex. 1JT-OLINCL-SN Olin Pendant w/ Clear Glass, Satin Nickel Finish

ACCESSORIES:

ADDITIONAL STEM SECTIONS:

Additional connecting stems are available to increase overall length, up to 10' max. Telescoping adjustable section allows up to 3" movement.

 T20A-SN or T20A-BR
 Adj. Section

 T203-SN or T203-BR
 3" Section

 T206-SN or T206-BR
 6" Section

 T212-SN or T212-BR
 12" Section

 T218-SN or T218-BR
 18" Section

LONGER CORD LENGTHS:

Longer cord length of 15' available. Add an "L" to the end of the item number, i.e. 1JC-169707-SNL.

CORD SLEEVES:

If concealing the cord is desired, order our 0.25" dia. metal sleeves. Each sleeve is 18" long and may be field cut.

T118-SN Satin Nickel T118-BR Bronze

STEMHOOKS:


Suspension hooks allow cord drops to be placed wherever desired. Suitable for sloped ceilings.

T103BR Bronze T103SN Satin Nickel

Project Information:


PENDANT OPTIONS:

MONOPOINT PENDANT CANOPY



- Flat or Dome Canopy styles. Dome style allows adjustment without cutting cord.
- Suitable for sloped ceilings
- Cord: 10' SVT, 5" sleeve at socketholder (V Series utilizes SJT-type)
- · Bronze or Satin Nickel

3BB or 3JB 3 LIGHT LINEAR CANOPY




- 2x stemhooks included
- Suitable for sloped ceilings
- Cords: 10' SVT, 5" sleeve at socketholder
- Bronze or Satin Nickel

3BC or 3JC 3 LIGHT ROUND CANOPY



- 3x stemhooks included
- 1.25 Suitable for sloped ceilings
 - Cords: 10' SVT, 5" sleeve at socketholder
 - Bronze or Satin Nickel

3BW or 3JW 3 LIGHT LARGE ROUND CANOPY




- 3x stemhooks included
- Suitable for sloped ceilings
- Cords: 10' SVT, 5" sleeve at socketholder
- Bronze or Satin Nickel

3BV or 3JV 3 LIGHT BAR CANOPY



- Some offset installation possible
- L.,25" Suitable for sloped ceilings
 - Cords: 10' SVT, 5" sleeve at socketholder
- Bronze or Satin Nickel

6BC or 6JC 6 LIGHT ROUND CANOPY



- 6x stemhooks included
- Suitable for sloped ceilings
- Cords: 10' SVT, 5" sleeve
- Bronze or Satin Nickel

STEM PENDANT



- Swivel at canopy, suitable for sloped ceilings
- Includes telescoping section plus 4 connectable stem sections, (1x 3", 1x 6", 1x 12", 1x 18"), 10' max
- Bronze or Satin Nickel

HOW TO ORDER A MULTILIGHT FIXTURE

To order, simply place the 3 character multilight code (shown above) as the cord fixture option:

Example: 3BC-493007-SN

3 Light round, Copa Opal glass, Satin Nickel finish - pg. 63 of the catalog